



OXY S

ANTI-ODOR CARBON FILTER

THE INNOVATIVE
BREATH OF ECOLOGY

OXYS Sp. z o.o. is a rapidly developing firm which focuses on innovative technology solutions for environment protection and improvement of the life quality. The base of our activity is production of anti-odor carbon filter OXYS, which main function is to neutralise the negative effects of odors coming from holding tanks, especially: inspection chambers, sewage pumping stations, and septic tanks. We concentrate on making individual solutions taking into account all the needs of our Customers.

We provide full professionalism and high level of engagement in realization of all projects. We investigate the market needs on our own, we design, we make and test devices in a way that they completely meet the most excessive requirements of our Customers.

As a producer of anti-odour filters OXYS, we offer all sorts of non-standard filters meeting our customers' requirements, both if it comes to materials used (PEHD, PCV, stainless steel) and various dimensions as well. OXYS Sp. z o.o. deals with collection, exchange and utilization activated carbon used, providing complete Customer service of required documentation.



FILTER FITTED UNDER MANHOLE COVERS



Anti-odor filter fitted under manhole cover is installed directly under manhole cover. After taking off the cover it is enough to place the filter on the circuit of the main frame of the manhole.



FILTERS FOR ROUND COVER	OXYS 315	OXYS 400	OXYS 600	OXYS 800
Mounting hole diameter [mm]	315	400	600	800
Lenght of the filter chamber [mm]	500	500	340	340
Weigth of the filter element [kg]	4,4 kg	5,3 kg	10,5 kg	10,5 kg

FILTERS FOR SQUARE COVER	OXYS K600	OXYS K800	OXYS K1000
Mounting hole diameter [mm]	600x600	800x800	1000x1000
Lenght of the filter chamber [mm]	340	340	340
Weigth of the filter element [kg]	10,5 kg	10,5 kg	13,3 kg

INTERNAL FILTERS FOR SEWAGE PUMPING STATIONS VENTS AND WASTE STACKS

The anti-odour chimney filter is mounted directly in the ventilation hole. The outside diameter is adjusted to PCV sleeve pass or four-lip gasket.



INTERNAL FILTERS FOR SEWAGE PUMPING STATIONS	OXYS W90	OXYS 110	OXYS W140	OXYS 160
Filter diameter [mm]	90	110	140	160
Lenght of the filter chamber [mm]	1000	1000	1000	1000
Mounting hole diameter [mm]	110	110	160	160
Weigth of the filter element [kg]	2,2 kg	4,3 kg	6,2 kg	8,8 kg

CARE FOR THE **NATURAL ENVIRONMENT**

IMPROVE YOUR **LIFE COMFORT**

PROTECT **YOUR HEALTH** AND THE HEALTH
OF **YOUR ENVIRONMENT**

CHOOSE **THE INNOVATIVE BREATH**
OF THE **ECOLOGY**

A photograph of a park with a winding path and trees. In the foreground, an open circular air filter unit is visible, with the brand name 'OXYS' printed on its lid. The filter is installed in a grassy area with fallen leaves.

OXYS SP. Z O.O.
UL. PARKOWA 36
42-622 ŚWIERKLANIEC
POLAND
PHONE: 0048 604-659-006
WWW.FILTRYOXYS.EU
EMAIL: BIURO@FILTRYOXYS.EU